

TrimLineSeries™ RECESSED SANITARY NAPKIN DISPOSAL

B-3513

Specify Finish Required \square Stainless Steel, Satin Finish ☐ Matte Black Finish, please use model no. 3513.MBLK (204mm) Finish Face of Wall-5-7/8" 3-11/16" (149mm) (93mm) 7/16"→ (76mm) -2-3/16" Operable Part (56mm) (11mm) ğ Recommended Mounting Height for Universal Design 14-1/16 11-7/8' (357mm) (301mm) 4-7/16" **Rough Wall Opening** 2-7/16" (113mm) 6-3/8" (162mm) wide (76mm) (63mm) 12-3/8" (314mm) high Finished Face of Floor 3-3/4" (95mm) min depth

MATERIALS:

Cabinet — 18-8, Type-304, heavy-gauge stainless steel. All-welded construction. Exposed surfaces have satin finish or matte black, as specified.

 \mathbf{Door} – 18-8, Type-304, 20-gauge (0.9mm) stainless steel with satin finish or matte black, as specified. Secured to cabinet with two rivets and equipped with a magnet catch.

Waste Receptacle — HDPE Plastic. Removable for servicing. Capacity: 0.6-gal. (2.3-L).

OPERATION:

To service waste receptacle, unlatch door and remove waste container. Cable door-swing limiter prevents damage to washroom accessories and walls.

INSTALLATION:

Provide framed rough wall opening 6-3/8" wide x 12-3/8" high (162×314 mm). Minimum recessed depth required from finish face of wall is 3-3/4" (95mm). Allow clearance for construction features that may protrude into rough wall opening from opposite wall. Coordinate with mechanical engineer to avoid pipes, vents, and conduits in wall. Mount cabinet with shims between framing and cabinet at all points indicated by an S, then secure unit with (4) #10 x 1-1/4" (4.8×32 mm) sheet-metal screws (not furnished).

Replacement Parts:

Skirt Replacement Kit 35139-53 Waste Receptacle Replacement 3517-60 International Label 3533-44

SPECIFICATION:

Recessed sanitary napkin disposal shall be Type-304 stainless steel with all-welded construction; exposed surfaces shall have satin finish or matte black, as specified. Door shall be Type-304, 20-gauge (0.9mm) stainless steel with satin finish or matte black, as specified. Secured to cabinet with two rivets and equipped with a magnet catch and cable door-swing limiter. Waste receptacle shall be HDPE plastic with a capacity of 0.6-gal. (2.3-L).

Recessed Sanitary Napkin Disposal shall be Model B-3513 of Bobrick Washroom Equipment, Inc., Clifton Park, New York; Jackson, Tennessee; Los Angeles, California; Bobrick Washroom Equipment Company, Scarborough, Ontario; Bobrick Washroom Equipment Pty. Ltd., Australia; and Bobrick Washroom Equipment Limited, United Kingdom.