

BIOFIL 2 month shower filter

Ref. 20261

Sterile



DESCRIPTION

BIOFIL 2 month shower filter - Ref. 20261

BIOFIL anti-Legionella and all-germ shower head filter.

Device material: ABS

Type of membrane: tubular microfiltration.

Membrane made from polyethylene.

Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.

Qualified water volume per duration of use: 6,000 litres.

Filtration flow rate: 6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar

(filter only, excludes any flow rate restriction in the tap).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 2 months after installation.

Resistance to thermal shocks: 70°C for 30 minutes.

Resistance to chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total).

Sterile filter. Individually wrapped, sterile.





CE Class Is medical device.

Weight: empty filter 105g / full filter 186g.

Single reference. Must be ordered in quantities of 10. Packaged in boxes of 10 units.

TECHNICAL CHARACTERISTICS

BIOFIL 2 month shower filter - Ref. 20261

| | |
|------------|---|
| Connector | M1/2" |
| Technology | Filtration terminale |
| Height | 62mm |
| Flow rate | 6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar |
| Diameter | 56mm |
| Lifespan | 2 months |
| Norms | ACS     |

ADVANTAGES



Anti-Legionella and all-germ



Space saving



Lifespan: 2 months after installation



Easy to install without tools

