

## TEMPOMATIC shower panel

Ref. 452300

Electronic






### DESCRIPTION

#### TEMPOMATIC shower panel - Ref. 452300

Electronic shower panel:  
Anodised aluminium shower panel for wall-mounted, exposed installation.  
With top inlet via in-line stopcock, M1/2".  
TEMPOMATIC electronic mixer for mixed water supply.  
Battery-operated with 223 6V Lithium battery.  
Infrared presence detection. Shower starts when hand is at 4cm from the sensor.  
Shuts off on demand or automatically after ~60 seconds.  
Duty flush (~60 seconds every 24 hours after the last use).  
Flow rate set at 6 lpm at 3 bar.  
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
Concealed fixings.  
Filter.  
10-year warranty.

### TECHNICAL FEATURES

#### TEMPOMATIC shower panel - Ref. 452300

Supply	6V battery
Connector	M1/2"
Technology	Electronic
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Finish	Aluminium
Standards and certifications	 
Warranty	

### ADVANTAGES



Total hygiene: operate without manual contact



Automatic flush anti-bacterial proliferation

