

TEMPOMIX time flow shower mixer

Ref. 790218

Time flow single control, kit 2/2







DESCRIPTION

TEMPOMIX time flow shower mixer - Ref. 790218







Recessed time flow shower mixer kit 2/2:
 Tamperproof bright polished stainless steel control plate 160 x 220mm.
 TEMPOMIX 3/4" single control shower mixer.
 Ligature-resistant collar.
 Temperature control and operation via the control.
 Maximum temperature limiter (can be adjusted by the installer).
 Time flow ~30 seconds, soft-touch operation.
 Flow rate 12 lpm at 3 bar, can be adjusted.
 Concealed fixings, stopcocks M1/2".
 Chrome-plated metal control.
 Integrated non-return valves and filters.
 30-year warranty.
 Order with recessed waterproof housing ref. 790BOX.

ADVANTAGES

-  80% water savings
-  Soft-touch operation
-  Installation recessed in wall
-  System tested to over 500,000 operations

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower mixer - Ref. 790218

Connector	1/2"
Technology	Time flow
Height	160mm
Depth	130mm
Width	220mm
Flow rate	12 lpm
Finish	Bright polished stainless steel
Norms	     
Warranty	