

SECURITHERM shower panel

Ref. 792413

Electronic battery-operated thermostatic






DESCRIPTION

SECURITHERM shower panel - Ref. 792413





SECURITHERM electronic thermostatic shower panel:
 Large stainless steel panel for wall-mounted, exposed installation.
 SECURITHERM thermostatic mixer.
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
 Anti-scalding safety: automatic shut-off if cold or hot water supply fails.
 Thermal shocks are possible.
 Battery-operated with 223 6V Lithium battery.
 Shower starts when hand is 4cm from the infrared sensor.
 Shuts off on demand or automatically after ~60 seconds.
 Duty flush (~60 seconds every 24 hours after the last use).
 Flow rate 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
 Concealed fixings.
 Filters and non-return valves.
 M1/2" stopcocks.
 10-year warranty.

TECHNICAL FEATURES

SECURITHERM shower panel - Ref. 792413

| | |
|------------------------------|---|
| Supply | 6V battery |
| Connector | M1/2" |
| Technology | Electronic |
| Height | 1220mm |
| Depth | 100mm |
| Width | 250mm |
| Flow rate | 6 lpm |
| Temperature limiter | Thermostatic |
| Finish | Stainless steel |
| Standards and certifications |   |
| Warranty |  |

ADVANTAGES

-  Total hygiene: operate without manual contact
-  Automatic flush anti-bacterial proliferation
-  Thermostatic control
-  Instant shut-off if cold water supply fails

