KOMPACT TC washbasin and floor-standing WC combination

Ref. 166700

Polished satin 304 stainless steel, cross wall - floor mount WC on LHS



ADVANTAGES



Bacteriostatic 304 stainless steel



Suitable for secure sector

DESCRIPTION

KOMPACT TC washbasin and floor-standing WC combination - ${\sf Ref.\,166700}$

Combination unit: washbasin and floor-standing WC pan on left sidewith recessed toilet roll holder.

Service duct installation (through-the-wall).

Bacteriostatic 304 stainless steel.

Polished satin finish.

Stainless steel unit thickness: 2mm.

Rounded corners and edges for improved safety.

Smooth surface for easy cleaning.

Suitable for prisons, police stations, etc.

WC pan is completely welded to washbasin, no screws:

makes cleaning easier and prevents concealment of objects.

Washbasin equipped with time flow tap: stainless steel tamperproofpush-

button and anti-blocking system, 7 second time flow, M1/2".

WC equipped with time flow flush valve, 7 second time flow, M3/4".

Water inlet: washbasin M1/2", WC M3/4".

Recessed horizontal water outlet: Ø 100mm.

200mm threaded rod can be cut to size (other lengths available on demand).


Weight: 30kg.

[Formerly ref: 0616130007]

TECHNICAL FEATURES

KOMPACT TC washbasin and floor-standing WC combination - Ref. 1

Height	1000mm
Length	615mm
Width	725mm
Thickness	2mm
Finish	304 polished satin stainless steel



© DELABIE https://www.delabie.com