BINOPTIC electronic tap

Ref. 398015

Mains



DESCRIPTION

BINOPTIC electronic tap - Ref. 398015

Deck-mounted electronic basin tap:

Independent IP65 electronic control unit.

230/12V mains supply with transformer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use). Active, infrared presence detection, sensor at the end of the spout optimises

Active, infrared presence det detection.

Chrome-plated brass body.

PEX flexible with filter and solenoid valve M3".

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Spout with smooth interior and low water volume (reduces bacterial development).

Drop height 250mm, for countertop washbasins.

Suitable for people with reduced mobility.

10-year warranty.

ADVANTAGES



90% water savings



Total hygiene: no manual contact



Anti-bacterial proliferation duty flush




Sleek design

TECHNICAL FEATURES

BINOPTIC electronic tap - Ref. 398015

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	250mm
Spout length	185mm
Flow rate	3 lpm
Warranty	TO MANAGEMENT



© DELABIE https://www.delabie.com