


- Tubes in robust, easy-to-clean stainless steel AISI 304, satin finished and brushed or structured
- All rails TÜV-certified in accordance with DIN EN 12182, and CE-marked in accordance with 93/42 EEC
- All rails capable of supporting weight up to 125 kg
- Outer diameter of tubes 32 mm for ergonomic hold
- Bend radii 75 mm
- Clearance from wall 106 mm
- Wall mountings for grab rails with 8-point mounting plate – can be freely rotated; for support rails with 6-point mounting plate; all mounting plates 4 mm thick  
With 2K - wallsealing-disc.
- Concealed fixings 75 mm in diameter, anti-theft, with silicone sealing ring at tube joint
- Mounting components for grab rails included in delivery
- On request intermediate sizes also available

## Grab rail



### Suggested text for specifications:

Grab rail in stainless steel, tube diameter 32 mm, satin or structured finish, clearance from wall 106 mm, TÜV-certified, CE-marked, supports weight up to 125 kg, concealed fixings by self-locking roses, includes mounting components.

Length ..... mm

Surface .....

Article No. BF 600

	Satin	Structured
Dimensions	ID number	ID number
300 mm	600 300	600 310
400 mm	600 400	600 410
500 mm	600 500	600 510
600 mm	600 600	600 610
1000 mm	601 000	601 010

